





# BH55 25x108

## **Gasoline breaker**

The entry-level model for demolition

The BH55 petrol demolition hammer is the entry-level model among the demolition hammers. Lighter and smaller than the other demolition hammers in the Wacker Neuson series, it is designed for professional use and impresses with its compact size and easy handling.

## Highlights

- High single stroke impact energy at a low weight
- Hood spring mounting
- Powerful, sturdy percussion system
- Stable, well-balanced handle

#### **Technical Data**

### Mechanical - Output Details

Number of blows	1.300,0 1/min
Singel beat energie	55,0 J
Transmission	Centrifugal Clutch - Single-level spur gear unit - pneumatic striking mechanisms
Mechanical Details	
Length without tool	791,0 mm
Width without tool	492,0 mm
Depth without tool	346,0 mm
Weight	22,70 kg
Tool holder	Hex 25x108
<ul><li>Engine</li></ul>	
Effective power	1,6 KW
Nominal Engine speed	4.250,0 1/min
Environment Data	
Storage temperature range	-30 - 50 °C

Operating temperature range	-10 - 40 °C
Sound level LpA	101,0 dB(A)
Sound level LpA (Standard)	DIN EN ISO 11201
Sound power LWA, measured	108,0 dB(A)
Sound power LWA, guaranteed	109,0 dB(A)
Sound power LWA (Standard)	2000/14/EG
Vibration total value ahv	8,3 m/s2
Vibration value (Standard)	DIN EN ISO 28927
Uncertainty in measurement HAV	3,0 m/s2
<ul><li>Electrical System</li></ul>	
Breaker Switch On/Off	Pushbutton OFF
<ul> <li>Operating Fluids</li> </ul>	
Lubricant	Gadus S3 V220C 2
Lubrication intervall	20,0 h

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.